



Aerite™ Feed Transporter

Specifications

Capacity:		<ul style="list-style-type: none"> - 1 x Bulk Bag = 2,200 lbs (1 tonnes) - 5 x 55 lb (22 kg) bags = 275 lbs (110 kg)* <p><i>*Loading in this manner will see the system distribute product as fast or faster than it is loaded.</i></p>
Discharge Rate:		Eleven (11) tonnes per hour.
Weight:	Feed transporter:	800 lbs. (363 kg).
	Switch gate:	20 lbs. (9 kg).
	Cyclonic decelerator:	Weight varies by model size.
Dimensions: (w x h x l)	Feed transporter:	102 cm x 102 cm x 168 cm or 40 in x 40 in x 66 in
	Switch gate:	30.5 cm x 16.5 cm x 54 cm or 12 in x 6.5 in x 21 in
	Cyclonic decelerator:	Various dimensions based on model.
Power:		<ul style="list-style-type: none"> - 20 hp Kohler gas motor complete with electric start, gel cell battery and 5 gallon (20 liter) auxiliary fuel tank. - Motor coupled to a positive displacement blower using a double belt system. Blower fitted with inlet silencer.
Materials:	Feed transporter:	<ul style="list-style-type: none"> - All lifting, support framing and safety guard structures manufactured of coated HSS steel. - Hopper and lid manufactured of marine grade aluminum. - Feed chute stainless steel and HDPE.
	Switch gate:	Marine aluminum, stainless steel flex hose, cast almag aluminum, HDPE and surgical rubber seals.
	Cyclonic decelerator:	Marine aluminum
Options:		<ul style="list-style-type: none"> - 20 Hp Honda gas motor; - Diesel power; - Larger loading hopper

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.

1415 Dominion Street, North Vancouver BC, V7J 1B3, Canada

Tel.: 1-604-924-1844 - Fax.: 1-604-924-1848 - E-mail: info@iasproducts.com - www.iasproducts.com