



AeriteBlower™ AB-180

Specifications

Blower Impellor:	Cast Almag™ 45.7cm (18.0-inch) diameter with machined 2.86mm (1.125-inch) hub and 6.33mm (0.25-inch) diameter shaft key. Dynamically balanced.	
Backing Plate:	Cast Almag™ 61cm (24.0-inch) diameter. Mounting bolt pattern allows for alternate power sources	
Blower Housing:	Cast Almag™	
Inlet:	20.3cm(8.0-inch) diameter	
Outlet:	12.7cm (5.0-inch) diameter,	
Power Source:	-8 kW (11 HP) Gx340 Honda power plant c/w low oil alert. -Standard machined shaft and backing plate bolt patterns provides for alternative gas and electric power plants.	
Performance:	Motor Speed <i>In revolutions per minute (rpm)</i>	Volume of Air <i>In cubic feet per minute (cfm)</i> NO OUTLET MUFFLER
	3,000	1,475
	3,200	1,600
	3,400	1,680
	3,600	1,765
	3,800	1,830

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.
