



AeroSpreader™ S125

Feed Broadcaster

Specifications

Capacity:		125 kg (276 lbs)
Hopper Volume:		0.198 m ³ (7 ft ³)
Feed Sizes:		From 2 mm to 11 mm.
Broadcast Rate:		37.5 kg maximum (82.5 lbs) per minute of 9 mm feed pellets. <i>Note that feed delivery rates increase as feed pellet sizes decrease.</i>
Broadcast Range:		21.5 m (70 ft) with 9 mm pellets. <i>Broadcast distance can be adjusted by operator moving blower speed handle.</i>
Dimensions: (l x w x h)	Stationary model:	127 cm x 61cm x 99 cm or 50 in x 24 in x 39 in
	Mobile model:	127 cm x 81 cm x 104cm or 50 in x 32 in x 41 in
Tare weight (empty):	Stationary model:	64 kg (141 lbs)
	Mobile model:	77 kg (170 lbs)
Materials:		-Marine grade aluminum - Galvanized steel and stainless steel hardware. <i>Projected life of hopper five to seven years with reasonable care and maintenance</i>
Power Source:		4.8 Kw (6.5 HP) gasoline powered by Honda (model GX200) fitted with low oil alert.
Controls:		- Feed control handle and stainless rod connected to plastic slide feed gate; - Blower speed handle and cable connected to Honda or Kohler throttle linkage.
Safety Features:		- Exterior surfaces are "hand smooth"; - Controls placed at comfortable standing height; - All moving parts shielded with appropriate guards; - Ergonomic design with low lift height and bag tray to assist operator position feed bags, split, and fill hopper; - Low center of gravity insures stable operation.

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.

1415 Dominion Street, North Vancouver BC, V7J 1B3, Canada

Tel.: 1-604-924-1844 - Fax.: 1-604-924-1848 - E-mail: info@iasproducts.com - www.iasproducts.com



Options:		<ul style="list-style-type: none">- Honda GX200 may be ordered with electric start, a 3-ampere charge system, and a 32-amp gel cell battery positioned in a marine box;- A 4.4 Kw (6.0 Hp) gasoline powered Kohler® with low oil alert;- A 4.4 Kw (6.0 Hp) gasoline powered Kohler® with low oil alert, electric start and 10-ampere charge system and 32-amp gel cell battery in a marine battery box.
----------	--	---

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.
