AutoSpreader™ Hatchery Feeder

Specifications

Capacity: *(standard)*	S44:	44 kg (97 lbs)
	S66:	66 kg (164 lbs)
Dimensions: (l x w x h) *Alternative hopper sizes to suit site feed volume needs are available.*	S44:	28 cm x 46 cm x 61 cm or 11 in x 18 in x 24 in
	S66	41 cm x 61 cm x 61 cm or 16 in x 24 in x 24 in
Feed Sizes:		Crushed to 6 mm.
Broadcast Rate:		1/50 revolution per minute managed using automatic controller for continuous or timed release over 24 hr clock.
Broadcast Volume:		Variable volumes– adjustable by controller time set up and dependent upon total feed delivery tube length.
Broadcast Range:		A full face feed drop across the entire tank surface.
Feed Delivery Tube Length:		Variable – from 3 ft (1m) to 40 ft (12.5m)
Materials:		- Marine grade aluminum; - Stainless steel auger; - Heavy walled PVC auger tube.
Power Source:		- 120 to 240 volt AC 60 Hz. - 50 Hz available.
Drive Components:		- Sealed end bearing on auger - Browning coupling between motor shaft and auger shaft.

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.

1415 Dominion Street, North Vancouver BC, V7J 2B3, Canada
Tel.: 1-604-924-1844 - Fax.: 1-604-924-1848 - E-mail: info@iasproducts.com - www.iasproducts.com