



Aerite™ MiniMax

Specifications

Hopper Capacities:	-500 kg (662 lb) standard - 1000 kg (2200 lb) -2000 kg (4500 lb) -Special sizes to 6000 kg (13000 lb)
Hopper Options:	Split hopper
Feed sizes	2 mm to 13 mm
Broadcast Rate:	Adjustable from 1 to 200 lb per minute
Delivery Rate:	Rate is based on size of rotary valve chosen
Dimensions: (l x w x h)	122cm x 107 cm x 137 cm or 48 in x 42 in x 54 in
Tare weight:	204 kg/450 lb
Power source:	-Electric: 220 to 600 VAC @ 50/60 Hz -Gas and diesel power systems available
Control:	-Manual: hopper slide feed gate; -Programmable Logic Controller(PLC): Feed gate, frequency, volume, cumulated daily total delivery
Features:	-Slide and stow lid ensures a 100% clear hopper opening for easy loading; -All surfaces "hand smooth"; -Sound dampening panels (optional) further reduce operating noise; -Full guards and shields.

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.