



## **SeeBrite™ MH 1000**

### **Underwater Lighting System**

**Metal Halide**

### *Specifications*

Lamp:	Watt	1000
	Bulb	BT 37
	Base	Mogul
	Rated Av. Life (hr)	20,000
	Initial Lumens	120,000
	CRI	70
	CCT (K)	4000
Ballast:	Input Volts	120/240
	Circuit Type	CWI
	Amps 120/240	9.0/5.25
	Height (cm)	30.5
	Width (cm)	17.8
	Weight (kg)	15
	CSA Certification	yes
Cable:	Length (m)	20/30
	Dimensions	0.048 O.D
	Jacket Construction	Polyurethane Safety Red
	Construction (mm)	65 x 0.245 tint plated copper
	Gauge	2/12
Light Head:	Construction	Black Delrin™
	Length (with cage)	4.95 cm (19.5 in)
	Width (with cage)	20.3 cm (8.0 in)
	Weight (with cage)	10.0 kg (22.0 lbs)
	Safety cage	Type 316 stainless steel
	Dome	Boron silicate glass 7cm (2.75-inch) diameter 6.0 mm (15/64 in) wall thickness
	Centering guide	Extreme temperature fiber board
Plugs:		600 volt @ 25 amp, IP68 rated to 33ft/10m for 14 days

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.