



SeeBrite™ MH 250

Underwater Lighting System

Metal Halide

Specifications

Lamp:	Type	T15
	Watt	250
	Base	Mogul
	Rated Av. Life (hr)	20,000
	Approximate Lumens	21,000
	CRI	65
	CCT (K)	4000
Ballast:	Input Volts	120
	Circuit Type	CWI
	Amps	2.6
	Height (inch)	23.5
	Width (inch)	16.9
	Weight (kg)	13
	CSA Certification	yes
Cable:	Length (ft)	20/30
	Dimensions (inch)	0.048 O.D
	Jacket Construction	Polyurethane Safety Red
	Gauge	2/14
Light Head:	Construction	Black Delrin™
	Length (with cage)	30.5cm (12.0- inch)
	Width (with cage)	13.0cm (5.0- inch)
	Weight (with cage)	1.4 kg. (3 lbs.)
	Safety cage	Type 316 stainless steel
	Dome	Boron silicate glass 7cm (2.75- inch) diameter 5mm (3/16-inch) wall thickness
	Centering guide	Extreme temperature fiber board
Plugs:		600 volt 32 ampere capacity IP68 rated with cap assembly

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.