



# **SeeBrite™ MH 400**

## **Underwater Lighting System**

### **Metal Halide**

### *Specifications*

Lamp:	Watt	400
	Bulb	ET18
	Base	Mogul
	Rated Av. Life (hr)	20,000
	Approximate Lumens	36,000
	CRI	65
	CCT (K)	<b>4000</b>
Ballast:	Input Volts	120/240
	Circuit Type	CWI
	Amps 120/240	4.05/2.05
	Height (in)	9.25
	Width (in)	6.65
	Weight (kg)	34
	CSA Certification	yes
Cable:	Length (m)	70 or 100
	Dimensions (cm)	0.048 O.D
	Jacket Construction	Polyurethane Red
	Conductors Count/Gauge	2/12
Light Head:	Construction	Black Delrin™
	Length (with cage)	10.5 inch/267 mm
	Width (with cage)	4.00 inch/100 mm
	Weight (with cage)	5.75 lb/2.61 kg
	Safety cage	Type 316 stainless steel
	Dome	- Boron silicate glass - 7.25 inch/ 18.42 mm long - 2.75 inch/70 mm wide
	Centering guide	Extreme temperature fiber board
Plugs:		- Non-Nema Bulgin 900 Series: 600 VAC @ 25-amp - 2-pin. IP68 rated to 33 ft / 10 meters for 14 days. - Fully field serviceable.

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.