



SeeBrite™ MHc 6000

Underwater Lighting System

Metal Halide Ceramic

Specifications

Lamp:	Watt	70
	Bulb	ED 17
	Base	Med.
	Rated Av. Life (hr)	15,000
	Approximate Lumens	6,000
	CRI	92
	CCT (K)	4000
Ballast:	Input Volts	20/277
	Circuit Type	Electr
	Amps 120/240	0.68/0.32
	Height (in)	3.25
	Width (in)	3.00
	Weight (kg)	3.58
	CSA/UL Certification	yes
Cable:	Length (m)	1.5
	Dimensions (cm)	0.32
	Jacket Construction	Polyurethane
	construction	41/35 copper
	Conductors Count/Gauge	3/16
Light Head:	Construction	Black Delrin™
	Length (with cage)	3.16 cm (12.5 in)
	Width (with cage)	1.45 cm (5.75 in)
	Weight (with cage)	3.1 kg (7.25 lbs)
	Safety cage	Type 316 stainless steel
	Dome	Boron silicate glass 7cm (2.75 in) diameter 6.0 mm (15/64 in) wall thickness
	Centering guide	Extreme temperature fiber board
Plugs:		-3-pin North American - Nema type -Other length available upon request

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.