



See Mate™ C4-12 **Integrated Video System**

Specifications

Dimensions:	Height:	1,500 mm (59.0 in)
	Width:	622 mm (24.5 in)
	Length:	660 mm (26.0 in)
	Weight:	55 kg (121 lbs)
Materials:	Frame	0.100 ga. marine aluminum welded box structure
	Wheels:	Pneumatic 254 mm x 89 mm or 10 in x 3.5 in
	Top Monitor Weatherproof Box: (h x w x l)	Powder paint coating 546 mm x 368 mm x 368 mm or 21.5 in x 14.5 in x 14.5 in
Electronics:	Circuit board:	- Solid state - no maintenance - Interchangeable quick connect harnesses - Battery strength indicator - LEDs Automatic low voltage (10.5-volt) shut off
	Breaker:	Main Power: 5 ampere Monitor: 3 ampere Aux. 1: 1 ampere Aux. 2: 1 ampere Camera 1-4: 1 ampere.
	Monitor:	- 15-inch colour - 12-volt DC - LCD flat screen
	Cameras:	Access any 1 of 4
	Resolution:	800 Lines
	Power:	- 12-volt DC one-(1) 48 ampere hour gel cell battery - Quick connect 2-pole plug - Regulated charger: 110-volt AC to 12-volt DC @ 10 amperes
	Options:	- 12-volt DC - One (1) 70 ampere hour gel cell battery - Quick connect 2-pole plug

Although IAS Products Ltd. makes every effort to ensure the accuracy of these product specification sheets at the time of publication, specifications for products described in this publication are subject to change without notice. No warrant for customer applications or usage is implied. IAS Products Ltd. makes no representation that the goods comply with any present or future federal, state, provincial, or local ordinance. Compliance is the Buyer's responsibility.